

AQT-KU40

GENERATING SET

(TECHNICAL DATA SHEET)



1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Kubota, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

Powered By:









"We deliver power, service and solutions in exactly the way you want."

Output Rating:

PRIME:	Ü	STANDBY:	
50 Hz—15	500 Rpm 400 V, 3ph		
36 kVA	28.8 kW	40 kVA	32 kW

ENGINE SPECIFICATIONS

ENGINE SI ECH ICATIONS	
Engine Make	KUBOTA
Engine Model	V3300-T-E2-BG
No. of Cylinders	4 vertical in-line
Cycle	4 Strokes
Induction System	Turbocharged
Cooling Method	Water cooled
Governing Type	Isochronous Electronic
Compression Ratio	21.8
Displacement	3.769 L
Bore/Stroke	100X120

ALTERNATOR SPECIFICATIONS

Alternator Make AC	QT I Leroy Somer I Stamford
Alternator Model AC	QT I TAL-042-F
Number of Poles 4	
Winding Pitch 2/3	3
Insulation Class - Temp Rise H	
Ingress Protection Rating IP	23
Excitation System SH	HUNT
AVR Model R1	120

COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

ALTERNATOR OPERATING DATA			
Over speed	2250 rpm		
Voltage Regulation	+ 1%		
Harmonic Coefficient THF	< 3.5%		
Tel. influence TIF	< 50		
Cooling air flow	0.1m3/ Sec		

Standard Specifications:

6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

7- Circuit Breaker:

3 pole LS MCCB

8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m	n 66db(A) @ 7mt

Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Generator/load current monitoring and protection (kW)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



DSE4520 MKII

AUTO START & AUTO MAINS FAILURE CONTROL

Dimensions:

Туре	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	1950	775	1175	100	850
CLOSED	2260	1110	1500	100	1350











Engine:



COOLING SYSTEM		
Total Coolant Capacity	(L) 13.2 L	
Cooling Fan Air Flow	0.1 m3/ min	
Radiator Fan Load	1.19	

LUBRICATION SYSTEM	
Total Oil Capacity	13.2 L
Oil Type	API-CH-4 or ACEA E5

EXHAUST SYSTEM	
Muffler Type	Industrial Grade
Max. Back Pressure	7.1
Exhaust Gas Flow (PRP/ESP)	9.99
Exhaust Gas Temperature	500

FUEL SYSTEM	
Recommended Fuel	Class A2 Diesel
Fuel Consumption 100%	8.61
Fuel Consumption 75% PRP	6.46

Optional configurations: Engine accessories: ☐ Heavy-duty air filter

ŏ	Coolant heater
П	Lubricant oil heater
П	Fuel and Water Separato
П	Lube oil rotary pump

Alternator	And	Access	sories:

ш	Lerby somer/stamora			
	Anti condensation heater			
	PMG + AVR \diamondsuit Double bearin	g		
	alternator High voltagekV			
	RTDs for Bearing and winding			
Cooling System:				
	55 degree Radiator			

Control System:

Remote Radiator

	AMF	
П	Parallel	
П	Practical type in low temperature environment	
П	Control Screen Heater	
й	Remote Annunciators	
П	Other (ComP, DEIF)	
_		
Circuit Breaker:		

Circ	Circuit Breaker:		
Ш	3/4 poles		
	Fixed/handcart type		
	Electric mechanism		

Automatic Transfer Switch (ATS):

	ATS cabinet
П	Contractor type ATS
Ĭ	Motorized changeover type ATS
Ctor	t Pattonu
Star	t Battery:
	Nickel-cadmium battery
	Maintenance-free battery
ă	Battery charger and selector switch
	Charging current meter
External Fuel Tank:	
	Single /double wall fuel tank (500-5000 L)
П	Fuel Transfer pump

Exhaust Muffler:

	Residential grade
	Critical grade
П	Hospital grade

Available for voltages :

☐ 400/230V, 480/277V, 380/220V, 440/254V, 416/240V,220/127V, 208/120V









Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.



Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





CONTACT US

Office 204, AI Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE

Call Us: +971 4 547 1703

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS











