

# AQT-CU900

**GENERATING SET** (TECHNICAL DATA SHEET)

# **Standard Specifications:**

#### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

#### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

#### 3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

#### Powered By:









"We deliver power, service and solutions in exactly the way you want."

# Output Rating:

0 01 010 010 11112	9.		
PRIME:		STANDBY:	
<b>5</b> 0 Hz—1500 Rpm	400 V, 3ph		
810 kVA		900 kVA	720 kW

# **ENGINE SPECIFICATIONS**

Engine Make	CUMMINS
Engine Model	QSK23-G3
Туре	4 cycle, 6-cylinder turbocharged
Bore mm	170 mm
Stroke Model	170 mm
Displacement	23.1 litre
Flywheel Dimensions	SAE 0
Battery Charging Alternator	35 amps
Starting Voltage	24 volt, negative ground
Fuel System	Cummins direct injection HPI
Fuel Filter	Spin-on fuel filters with water separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 103 Litres

#### ALTERNATOR SPECIFICATIONS

Alternator Make	AQT I Leroy Somer   Stamford
Alternator Model	AQT   TAL-049-C   S6L1D-D41
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	Н
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	MX321

## COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034,IEC 60947-2

	ALTERNATOR OPERATING DATA
Over speed	2250 rpm
Voltage Regulation	<u>+</u> 5%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	1.42 m3/ Sec

# **Standard Specifications:**

#### 6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours Built in fuel tank up to 800 kVA

#### 7- Circuit Breaker:

ACB - schneider

#### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- **Over Current**
- Under / Over Generator Voltage
- Low Oil Pressure
- **Emergency stop**
- High engine temperature

#### 9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

## **Acoustic Enclosure Specifications:**

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7n	n 66db(A) @ 7mt

# **Control System:**

Large back-lit text display

Multiple display languages

**DSENET** expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)

Breaker contol via fascia buttons

Fuel and start outputs, configurable using can

Generator/load current monitoring and protection (kW)

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



# DSE 6120

**AUTO START & AUTO MAINS** FAILURE CONTROL

# **Dimensions:**

Туре	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	4300	1750	2200	1170	6300
CLOSED	6000	2440	2590	1170	9300













# Engine:



COOLPAC PE	RFORMANCE DATA
Cooling System Design	Air-Air Charge Cooled
Coolant Ratio	50% ethylene gylcol; 50% water
Coolant Capacity (L)	110
Limiting Ambient Temp.	50.9 Degree Celsius
Fan Power Kw	14.4
Cooling System Air Flow (m3/s)	13.5
Air Cleaner Type	Dry replaceable element with restriction
	indicator

FUEL CONS	UMPTION 1500 (50 HZ)
Fuel Consumption @ 110%	178
Fuel Consumption @ 100%	161
Fuel Consumption @ 75%	121
Fuel Consumption @ 50%	85
Fuel Consumption @ 25%	46

# Optional configurations: Engine accessories: Heavy-duty air filter Coolant heater Lubricant oil heater Fuel and Water Separator Lube oil rotary pump **Alternator And Accessories:**

	Leroy somer/stamford
	Anti condensation heater
	PMG + AVR $\diamondsuit$ Double bearing
	alternator High voltagekV
	RTDs for Bearing and winding
Co	oling System:
	55 degree Radiator
	Remote Radiator

Con	trol System:
	AMF Parallel Practical type in low temperature environment Control Screen Heater Remote Annunciators Other (ComP, DEIF)
Circ	uit Breaker: 3/4 poles

	Electric mechanism
Aut	omatic Transfer Switch (ATS):
	ATS cabinet
П	Contractor type ATS
Ĭ	Motorized changeover type ATS
Star	t Battery:
	Nickel-cadmium battery
	Maintenance-free hattery

П	Wotonzed changeover type A13
Sta	rt Battery:
	Nickel-cadmium battery
	Maintenance-free battery
ă	Battery charger and selector switch
Ğ	Charging current meter
Ext	ernal Fuel Tank:
	Single /double wall fuel tank (500-5000 L)
	Fuel Transfer pump
Exh	aust Muffler:
П	Residential grade

EXN	aust iviumer:	
	Residential grade	
	Critical grade	
	Hospital grade	
Ava	Available for voltages :	
	400/230V, 480/277V, 380/220V, 440/254V	
	416/240V.220/127V. 208/120V	









#### **Our Success**

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.



Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

#### FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS











