

# AQT-CU110

GENERATING SET (TECHNICAL DATA SHEET)

#### **Standard Specifications:**

#### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

#### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

#### 3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type: brushless AC alternator

5- Radiator: 50°C, fan protective shroud

#### Powered By:







### "We deliver power, service and solutions in exactly the way you want."

#### **Output Rating:**

PRIME:		STANDBY:	
50 Hz—1500 Rpm	400 V, 3ph		
100 kVA	80kW	110 kVA	88 kW

ENGINE SPECIFICATIONS	
Engine Make	CUMMINS
Engine Model	6BTA5.9-G2
Туре	4 cycle, In-line, 6-Cylinder Diesel, Turbocharged
Bore mm	102 mm
Stroke Model	120 mm
Displacement	5.9 L
Flywheel Dimensions	3/11.5
Battery Charging Alternator	55 amps
Starting Voltage	12 volt
Fuel System	Direct injection
Fuel Filter	Spin on fuel filters with Water Separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 16.4 Litres
ALTERNATOR SPECIFICATIONS	
Alternator Make	AQT I Leroy Somer I Stamford

Alternator Make	AQT I Leroy Somer I Stamford
Alternator Model	AQT I TAL-044D I UCI274D
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	н
Ingress Protection Rating	IP 23
Excitation System	SHUNT
AVR Model	R120

#### COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

ALTERNATOR OPERATING DATA	
Over speed	2250 rpm
Voltage Regulation	+ 1%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	0.25 m3/ Sec



#### **Standard Specifications:**

#### 6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours running Built in fuel tank up to 800 kVA

#### 7- Circuit Breaker:

LS

#### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

#### 9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

#### Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011

Noise Pressure level @ 7m 66db(A) @ 7mt

## **Control System:**

- Large back-lit text display
- Multiple display languages
- DSENET expansion compatible
- Data logging facility
- Fully configurable via PC using USB communication
- Front panel configuration
- Efficient power save mode
- 3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVA h)



## Dimensions:

#### Length Width Height Fuel Tank Weight Туре (mm) (mm) (mm) (L) (KG) 775 190 1200 OPEN 2400 1375 2750 1495 190 1810 CLOSED 1100

Generator/load current monitoring and protection (kW)

Fuel and start outputs, configurable using can

Automatically transfers between mains (utility) and generator

4 configurable analogue/digital inputs

Increased input and output expansion capability via dsenet

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs

AUTO START & AUTO MAINS

DSE 4520

FAILURE CONTROL

Breaker contol via fascia buttons

4 configurable DC outputs



OT GENERATOR





## **Engine**:



#### COOLPAC PERFORMANCE DATA

Cooling System Design	Jacket Water cooled	
Coolant Ratio	50% ethylene gylcol; 50% water	
Coolant Capacity (L)	19.75	
Limiting Ambient Temp.	54 Degree Celsius	
Fan Power Kw	5.6	
Cooling System Air Flow (m3/s)	3.44	
Air Cleaner Type	Dry replaceable element with restriction	
	indicator	

FUEL CONSUMPTION 1500 (50 HZ)		
Fuel Consumption @ 110%	27	
Fuel Consumption @ 100%	25	
Fuel Consumption @ 75%	18	
Fuel Consumption @ 50%	12	
Fuel Consumption @ 25%	7	

## **Optional configurations:**

#### Engine accessories:

- Heavy-duty air filter Coolant heater
- Lubricant oil heater
- Fuel and Water Separator
- Lube oil rotary pump

#### **Alternator And Accessories:**

- Leroy somer/stamford
- Anti condensation heater
- PMG + AVR 🛇 Double bearing
- alternator High voltage \_\_\_\_\_kV
- RTDs for Bearing and winding

#### **Cooling System:**

- 55 degree Radiator
- Remote Radiator П

#### **Control System:**

- AMF
- Parallel
- Practical type in low temperature environment
- Control Screen Heater
- Remote Annunciators
- Other (ComP, DEIF)

## **Circuit Breaker:**

- 3/4 poles
- Fixed/handcart type П
- Electric mechanism

#### Automatic Transfer Switch (ATS):

- ATS cabinet
  - Contractor type ATS
- Motorized changeover type ATS

#### Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch
- Charging current meter

#### **External Fuel Tank:**

- Single /double wall fuel tank (500-5000 L)
- Fuel Transfer pump

#### **Exhaust Muffler:**

- Residential grade
- Critical grade
- Hospital grade

#### Available for voltages :

400/230V, 480/277V, 380/220V, 440/254V, 416/240V,220/127V, 208/120V



#### **Our Success**

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

#### **Objectives**

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

"We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements".



At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.





## **CONTACT US**

Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE Call Us: +971 4 547 1703 Email: info@aqtgenerators.com

#### FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS

