



القوة الذكية للتجارة ش. ذ. م. م
ALQWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

www.aqtgenerators.com

AQT-CU700

GENERATING SET
(TECHNICAL DATA SHEET)

Standard Specifications:

1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

4- Alternator Type:

brushless AC alternator

5- Radiator:

50°C, fan protective shroud

Powered By:



**LEROY
SOMER**

STAMFORD
power generation



"We deliver power, service and solutions in exactly the way you want."

Output Rating:

PRIME:		STANDBY:	
50 Hz—1500 Rpm	400 V, 3ph		
646 kVA	517 kW	700 kVA	560 kW

ENGINE SPECIFICATIONS

Engine Make	CUMMINS
Engine Model	VTA28-G5
Type	4 cycle, in-line, turbocharged and aftercooled, 12-cylinder
Bore mm	140 mm (5.50 in.)
Stroke Model	152 mm (6.00 in.)
Displacement	28 L
Flywheel Dimensions	SAE 0
Battery Charging Alternator	35 amps
Starting Voltage	24 volt
Fuel System	Direct Injection Cummins PT
Fuel Filter	Spin-on fuel filters with water separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 83 Litres

ALTERNATOR SPECIFICATIONS

Alternator Make	AQT Leroy Somer Stamford
Alternator Model	AQT TAL-047-E HCI544F/S5L1D-F41
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	H
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	AS440

COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

ALTERNATOR OPERATING DATA

Over speed	2250 rpm
Voltage Regulation	± 1%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	1.12m ³ / Sec



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com



القوة الذكية للتجارة ش. ذ. م. م
ALQWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

www.aqtgenerators.com

Standard Specifications:

6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours running
Built in fuel tank up to 800 kVA

7- Circuit Breaker:

LS

8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

9- Warranty policy:

- AQT GENERATOR products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVAr h)

Generator/load current monitoring and protection (kW)

Breaker control via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dseNET

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



DSE 6120

AUTO START & AUTO MAINS
FAILURE CONTROL

Dimensions:

Type	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	4175	1712.5	2375	1210	5785
CLOSED	5925	2305	2532.5	1210	8410



Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m	66db(A) @ 7mt



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com






القوة الذكية للتجارة ش. ذ. م. م
ALQWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

www.aqtgenerators.com

Engine:



COOLPAC PERFORMANCE DATA

Cooling System Design	Air-Air Charge Cooled
Coolant Ratio	50% ethylene glycol; 50% water
Coolant Capacity (L)	83
Limiting Ambient Temp.	50
Fan Power Kw	19.6
Cooling System Air Flow (m3/s)	12.5
Air Cleaner Type	Dry replaceable element with restriction indicator

FUEL CONSUMPTION 1500 (50 HZ)

Fuel Consumption @ 110%	154
Fuel Consumption @ 100%	NA
Fuel Consumption @ 75%	N/A
Fuel Consumption @ 50%	N/A
Fuel Consumption @ 25%	N/A

Optional configurations:

Engine accessories:

- ☐ Heavy-duty air filter
- ☐ Coolant heater
- ☐ Lubricant oil heater
- ☐ Fuel and Water Separator
- ☐ Lube oil rotary pump

Alternator And Accessories:

- ☐ Leroy somer/stamford
- ☐ Anti condensation heater
- ☐ PMG + AVR ◇ Double bearing
- ☐ alternator High voltage _____kV
- ☐ RTDs for Bearing and winding

Cooling System:

- ☐ 55 degree Radiator
- ☐ Remote Radiator

Control System:

- ☐ AMF
- ☐ Parallel
- ☐ Practical type in low temperature environment
- ☐ Control Screen Heater
- ☐ Remote Annunciators
- ☐ Other (ComP, DEIF)

Circuit Breaker:

- ☐ 3/4 poles
- ☐ Fixed/handcart type
- ☐ Electric mechanism

Automatic Transfer Switch (ATS):

- ☐ ATS cabinet
- ☐ Contractor type ATS
- ☐ Motorized changeover type ATS

Start Battery:

- ☐ Nickel-cadmium battery
- ☐ Maintenance-free battery
- ☐ Battery charger and selector switch
- ☐ Charging current meter

External Fuel Tank:

- ☐ Single /double wall fuel tank (500-5000 L)
- ☐ Fuel Transfer pump

Exhaust Muffler:

- ☐ Residential grade
- ☐ Critical grade
- ☐ Hospital grade

Available for voltages :

- ☐ 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com





القوة الذكية للتجارة ش. ذ. م. م.
ALQWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

www.aqtgenerators.com

Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

“We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements”.



AQT GENERATORS

At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.



القوة الذكية للتجارة ش. ذ. م. م.
ALQWA ALTHAKYA TRADING L.L.C

AQT GENERATORS

CONTACT US

Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE

Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS



WhatsApp



LinkedIn



Facebook



Instagram



TikTok



Youtube