



القوة الذكية للتجارة ش. ذ. م. م  
ALQWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

www.aqtgenerators.com

# AQT-CU1000

## GENERATING SET

### (TECHNICAL DATA SHEET)

#### Standard Specifications:

##### 1- Prime Rating:

Unlimited hours usage, with an average load factor of 80% over each 24 hour period. 10% overload is available for 1 hour in every 12 hours operation. 0 overload is permitted on standby power.

##### 2- Standby Rating:

Limited to 500 hours annual usage, with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.

##### 3- Engine:

Cummins, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.

##### 4- Alternator Type:

brushless AC alternator

##### 5- Radiator:


50°C, fan protective shroud

#### Powered By:



**LEROY  
SOMER**

**STAMFORD**  
power generation



*"We deliver power, service and solutions in exactly the way you want."*

#### Output Rating:

PRIME:		STANDBY:	
60 Hz—1800 Rpm 480 V, 3ph			
909 kVA	727 kW	1000 kVA	800 kW

#### ENGINE SPECIFICATIONS

Engine Make	CUMMINS
Engine Model	QSK23-G3
Type	4 cycle, 6-cylinder turbocharged
Bore mm	170 mm
Stroke Model	170 mm
Displacement	23.1 litre
Flywheel Dimensions	SAE 0
Battery Charging Alternator	35 amps
Starting Voltage	24 volt, negative ground
Fuel System	Cummins direct injection HPI
Fuel Filter	Spin-on fuel filters with water separator
Lube Oil Filter and Capacity (L)	Spin on full flow filter - 103 Litres

#### ALTERNATOR SPECIFICATIONS

Alternator Make	AQT   Leroy Somer   Stamford
Alternator Model	AQT   TAL-049-C   S6L1D-D41
Number of Poles	4
Winding Pitch	2/3
Insulation Class - Temp Rise	H
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	MX321

#### COMPLY WITH STANDARDS

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

#### ALTERNATOR OPERATING DATA

Over speed	2250 rpm
Voltage Regulation	+ 5%
Harmonic Coefficient THF	< 3.5%
Tel. influence TIF	< 50
Cooling air flow	1.42 m3/ Sec



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com



القوة الذكية للتجارة ش. ذ. م. م  
ALQWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

www.aqtgenerators.com

## Standard Specifications:

### 6- Fuel Tank:

Capacity of fuel tank is for 8-10 hours running  
Built in fuel tank up to 800 kVA

### 7- Circuit Breaker:

ACB - schneider

### 8- Control system alarms:

- Over and Under Speed
- Low and High Battery Volt.
- Start and Stop Failure
- Over Current
- Under / Over Generator Voltage
- Low Oil Pressure
- Emergency stop
- High engine temperature

### 9- Warranty policy:

- **AQT GENERATOR** products has a warranty for 12 Months or 1000 hours whichever occurs first against any manufacturing defects
- Wearing parts (filters), incorrect man made operation, maintenance failures are excluded from the warranty policy

## Control System:

Large back-lit text display

Multiple display languages

DSENET expansion compatible

Data logging facility

Fully configurable via PC using USB communication

Front panel configuration

Efficient power save mode

3 phase generator sensing

Accumulated power monitoring (kWh, kVA h, kVAr h)

Generator/load current monitoring and protection (kW)

Breaker control via fascia buttons

Fuel and start outputs, configurable using can

4 configurable DC outputs

4 configurable analogue/digital inputs

Automatically transfers between mains (utility) and generator

Increased input and output expansion capability via dseNET

IP65 rating (with optional gasket) offers increased resistance to water ingress

Digital inputs; Analogue Inputs



### DSE 6120

AUTO START & AUTO MAINS  
FAILURE CONTROL

## Dimensions:

Type	Length (mm)	Width (mm)	Height (mm)	Fuel Tank (L)	Weight (KG)
OPEN	4300	1750	2200	1170	6300
CLOSED	6000	2440	2590	1170	9300

## Acoustic Enclosure Specifications:

Enclosure Type	Acoustic & Weather Proof
Drainage Provision	Fuel and Water Drainage
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection Rating	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	TAL 9010
Base frame RAL Color	RAL 9011
Noise Pressure level @ 7m	66db(A) @ 7mt



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com





القوة الذكية للتجارة ش. ذ. م. م  
ALQWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

www.aqtgenerators.com

## Engine:



### COOLPAC PERFORMANCE DATA

Cooling System Design	Air-Air Charge Cooled
Coolant Ratio	50% ethylene glycol; 50% water
Coolant Capacity (L)	110
Limiting Ambient Temp.	55 Degree Celsius
Fan Power Kw	24.3
Cooling System Air Flow (m3/s)	16.6
Air Cleaner Type	Dry replaceable element with restriction indicator

### FUEL CONSUMPTION 1800 (60 HZ)

Fuel Consumption @ 110%	212
Fuel Consumption @ 100%	189
Fuel Consumption @ 75%	139
Fuel Consumption @ 50%	97
Fuel Consumption @ 25%	56

## Optional configurations:

### Engine accessories:

- ☐ Heavy-duty air filter
- ☐ Coolant heater
- ☐ Lubricant oil heater
- ☐ Fuel and Water Separator
- ☐ Lube oil rotary pump

### Alternator And Accessories:

- ☐ Leroy somer/stamford
- ☐ Anti condensation heater
- ☐ PMG + AVR ◇ Double bearing
- ☐ alternator High voltage \_\_\_\_\_kV
- ☐ RTDs for Bearing and winding

### Cooling System:

- ☐ 55 degree Radiator
- ☐ Remote Radiator

### Control System:

- ☐ AMF
- ☐ Parallel
- ☐ Practical type in low temperature environment
- ☐ Control Screen Heater
- ☐ Remote Annunciators
- ☐ Other (ComP, DEIF)

### Circuit Breaker:

- ☐ 3/4 poles
- ☐ Fixed/handcart type
- ☐ Electric mechanism

### Automatic Transfer Switch (ATS):

- ☐ ATS cabinet
- ☐ Contractor type ATS
- ☐ Motorized changeover type ATS

### Start Battery:

- ☐ Nickel-cadmium battery
- ☐ Maintenance-free battery
- ☐ Battery charger and selector switch
- ☐ Charging current meter

### External Fuel Tank:

- ☐ Single /double wall fuel tank (500-5000 L)
- ☐ Fuel Transfer pump

### Exhaust Muffler:

- ☐ Residential grade
- ☐ Critical grade
- ☐ Hospital grade

### Available for voltages :

- ☐ 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V



+971 4 547 1703



info@aqtgenerators.com



http://www.aqtgenerators.com





القوة الذكية للتجارة ش. ذ. م. م.  
ALQWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

www.aqtgenerators.com

## Our Success

We owe our success to our hardworking, highly skilled and committed employees. Our core focus lies in providing customized integrated products and services with well-established infrastructure, equipment and manpower to support and provide the turn key solutions for various industries. We provide the latest in power generator technology equipment, allowing us to give our customers the best product and the best possible service.

## Objectives

Our objective is to serve customers to the utmost by providing them with the best-in-class electric generators, reliable door to door delivery, and after sales service at competitive market prices.

**“We continue to build our solid reputation for excellence and response, while delivering reliable and tailored solutions to meet the customer's requirements”.**



**AQT GENERATORS**

*At AQT Generators, we take pride in being a dynamic force in the realm of diesel generator sets, offering an extensive range of international brands renowned for their reliability and performance. Our commitment to excellence is reflected in our partnerships with world-famous engine manufacturers such as Perkins and Cummins, coupled with top-notch alternators from Stamford and Leroy Somer.*



القوة الذكية للتجارة ش. ذ. م. م.  
ALQWA ALTHAKYA TRADING L.L.C

**AQT GENERATORS**

## CONTACT US

Office 204, Al Owais Building, Port Saeed, Plot No. 388-0, Dubai, UAE

Call Us: +971 4 547 1703

Email: info@aqtgenerators.com

## FOLLOW US ON OUR SOCIAL MEDIA ACCOUNTS



WhatsApp



LinkedIn



Facebook



Instagram



TikTok



Youtube